

# Marine Small GPS Antenna

## MODEL: MA-620-SMA(F)

Small size and ruggedness, demand of vehicle locating and marine navigation GPS antenna that will sustain harsh environment.



- Low noise figure
- Fully weather proof.
- Ultra-high Sensitivity
- Compact construction
- Excellent temperature stability

The antenna system **MA-620** is the integration of the high performance GPS patch antenna and a low noise amplifier into state-of-the-art low a very low profile/extremely compact/fully waterproof antenna signal enclosure. When connected to a GPS receiver with +3~5V DC antenna power it provide excellent signal amplification and out-band-rejection for that receiver.

### Features:

GPS antenna with double threaded bolts and through holes for cable routing with course & fine treaded pitch locking for wing-nut fastener and lock-nut to prevent vibrations and un-authorize removal.

### Specifications:

| PHYSICAL CONDITION |  |
|--------------------|--|
| Constructions:     | Polycarbonate radome,detachable cable/connector for easy mount, rubber-O-ring between top radome and screw base for waterproof |
| Dimensions:        | 60mm(Dia.) x 70mm(H)   |
| Weight:            | 200grams (w/o cable & connector).  |
| Color:             | Standard in ivory white, other colours available upon request.   |
| Mounting:          | Bulkhead mount with 0.8 inch threaded wing nut (standard accessory).   |
| Mounting Adapters  | Pole mount to 1"-14 UNS threaded mast  |
| Base mounting      | FB1 1"-14 UNS  |
| Cable & Connector  |  |

|   |   |
|---|---|
| RF cable:   | SMA(M) +10 meter RG58 +TNC(M) (standard) other length (optional)  |
| Pulling strength:   | 6 Kg @ 5sec. molded plastic on connector end for strain relief.   |
| Connector   | SMA(F)  |
| <b>Antenna Element</b>  |   |
| Center Frequency:   | 1575.42 MHz +/-1.023 MHz  |
| Polarization:   | R.H.C.P. (Right Handed Circular Polarization).  |
| Absolute Gain @ Zenith:   | +5 dBi typical.   |
| Gain @ 10° Elevation:   | -1 dBi typical.   |
| Axial Ratio:  | 3 dB max.   |
| Output VSWR:  | 1.5 max   |
| Output Impedance:   | 50 ohm  |
| <b>Low Noise Amplifier</b>  |   |
| Center Frequency:   | 1575.42 MHz   |
| Power Gain:   | 28db +/-4.5db   |
| Bandwidth:  | 2 MHz min.  |
| Noise Figure:   | 1.5 min.  |
| Outer Band Attenuation:   | 20 dB min. @ Fo +/-50 Mhz.  |
| Supply Voltages:  | 2.5~5.5V DC.  |
| Current Consumption:  | 2.5V : 6.6mA Typ.<br>3V: 8.6mA Typ.<br>4V: 12.6mA Typ.<br>5V: 16.6mA Typ.                                   |
| Output Impedance:   | 50W ohm   |
| <b>Overall Performance: (antenna element, LNA &amp; coax cable)</b> |   |
| Center Frequency:   | 1575.42 Mhz.  |
| Gain:   | At 90° vertical to sky 30 ± 4.5dBi<br>(cable loss) Note:1<br>Mounted on the 60mm x 60mm square ground plane |
| Noise Figure:   | 2.0 max.  |
| Axial Ratio:  | 3 dB max.   |
| Bandwidth:  | 2MHz min.   |
| VSWR:   | 2.0 max.  |
| Output Impedance:   | 50W ohm   |
| <b>Environmental</b>  |   |
| Operating Temperature:  | -40°C~ +85°C.   |
| Storage Temperature:  | -50°C~ +90°C.   |
| Relative Humidity:  | 95% non-condensing.   |
| Water Resistance:   | 100% waterproof.  |

\* This specification is subject to change without prior notice

Data Updated: FEB.01, 2010

