

Omni-Directional GSM Antenna

MODEL: TH-260-GSM



GENERAL DESCRIPTION

Model No	P/N
	TH-260-GSM

Below is a table summarizing the antenna design specification.

1.1 Electrical Properties

Parameter	Description
Frequency Band	824~960/1710~1990/1990~2170Mhz
Nominal Impedance	50 ohm
Polarization	Vertical
Return Loss	Please See Data-1
V.S.W.R	2.0:1
Antenna Average Gain	4~5 dBi
Note: Gain includes the cable loss	

1.2 Mechanical Properties

Parameter	Description
Antenna Type	External Antenna
Touch Type	Screw Type

Connector Type	FME 180°(Female) or SMA-M
Antenna Dimensions	490 mm ± 5
Antenna Cable Total Length	RG-58 /U 5000 mm ± 20
Antenna Color	Black
Operating Temperature Range	-20°C~+60°C
Storage Temperature Range	-30°C~+70°C

1. Appearance

NO.	NAME	FINISH	Q. TY
01	Plug cap	Black	01
02	Tubing plastic	Black	01
03	Fixed set	Nickel plating	01
04	Piece clamping	Gray	01
05	Claw washer	Nickel plating	01
06	Hexagonal nut	Nickel plating	01
07	RG-58 A/U Cable	Black	01
08	FME 180°(Female)	Nickel plating	01
09	Heat-shrink tube	Black	01

FREQUENCY: 824-960/1710-1990/1990-2170Mhz.

 Third angle projection	CUSTOMER' S	MODEL	PARTS NUMBER	FREQUENCY	UNIT	SCALE	DATE	VERSION
					M/M		20090205	1
	TOLERANCE	X. XX±0. 15	NAME	PARTS NUMBER	APPROVED	CHECKED	DRAWING	DESIGNED
	SURFACE ROUGHNESS	 S	APPEARANCE					

2. Frequency

